## WHAT IS CLAIMED IS:

5

20

25

35

- 1. A mixing/charging port for medical treatment comprising a disk-like valve having an insertion hole at the center,
- a seating for supporting a lower part of the periphery of the valve with the center of the rear surface side of the valve left unsupported, and
- a cover for restraining the valve by covering at least an upper part of the periphery of the valve with the center of the front surface side of the valve left uncovered, wherein:
- a fitting hole defined by an inner edge portion of the cover works as an anchor for anchoring an insertion member to the mixing/charging port in a way in which the insertion member is fitted to the fitting hole when the insertion member is inserted into the insertion hole; and
- a tip of a depressed part of the valve is brought into contact against an inner bottom surface of the seating when the valve is depressed by the insertion member.
  - 2. The mixing/charging port for medical treatment according to claim 1, wherein an inner side surface of the seating is formed so as to have the same shape as the shape of the valve in a state in which the valve is depressed by the insertion of the insertion member.
  - 3. The mixing/charging port for medical treatment according to claim 1, wherein a groove is provided in the direction of the flow through the inner part of the mixing/charging port and a bottom part of the groove is located at a lower level relative to the bottom surface of the seating.
- The mixing/charging port for medical treatment according to claim 2, wherein a groove is provided in the direction of the flow through the inner
  part of the mixing/charging port and a bottom part of the groove is located at level to the bottom surface of the seating.
  - 5. The mixing/charging port for medical treatment according to claim 3, wherein the cross-sectional shape of the groove corresponds to a shape defined by an arc and chord at an opening part of the passage.
    - 6. The mixing/charging port for medical treatment according to claim 4,

wherein the cross-sectional shape of the groove corresponds to a shape defined by an arc and chord at an opening part of the passage.